

**Jawahar Naovdaya Vidyalaya, Chhan (Raj.)
Water Treatment Plants AMC Tender rates**

Name of items & Description	Rate including all taxes without material																						
<p><u>RO Plant 50 LPH</u></p> <table border="1"> <tr> <td></td> <td>45-55 Ltr/hr</td> </tr> <tr> <td>Max Duty Cycle</td> <td>240-300 Ltr/Day</td> </tr> <tr> <td>Filter Cartridges</td> <td>Sediment, GAC, CTO, Post Carbon</td> </tr> <tr> <td>RO Membrane</td> <td>75/80 GPD x 4 No.</td> </tr> <tr> <td>Pump</td> <td>150 GPD x 2 No.</td> </tr> <tr> <td>Input Voltage</td> <td>150-300 V AC (50 Hz)</td> </tr> <tr> <td>Operating Voltage</td> <td>24 V DC/36 V - 2A DC</td> </tr> <tr> <td>Input TDS</td> <td>Upto 2000 ppm</td> </tr> </table>		45-55 Ltr/hr	Max Duty Cycle	240-300 Ltr/Day	Filter Cartridges	Sediment, GAC, CTO, Post Carbon	RO Membrane	75/80 GPD x 4 No.	Pump	150 GPD x 2 No.	Input Voltage	150-300 V AC (50 Hz)	Operating Voltage	24 V DC/36 V - 2A DC	Input TDS	Upto 2000 ppm							
	45-55 Ltr/hr																						
Max Duty Cycle	240-300 Ltr/Day																						
Filter Cartridges	Sediment, GAC, CTO, Post Carbon																						
RO Membrane	75/80 GPD x 4 No.																						
Pump	150 GPD x 2 No.																						
Input Voltage	150-300 V AC (50 Hz)																						
Operating Voltage	24 V DC/36 V - 2A DC																						
Input TDS	Upto 2000 ppm																						
<p><u>RO Plant 500 LPH</u></p> <table border="0"> <tr> <td><u>Description</u></td> <td><u>Features</u></td> </tr> <tr> <td>Technology</td> <td>: Membrane Based, (Size: 40x40)</td> </tr> <tr> <td>Electricity</td> <td>: 1680W/Ac-220v/440v, 50Hz</td> </tr> <tr> <td>Pre Filtration</td> <td>: Suspended Solids, Chemical Impurities, Bacteria like Cryptosporidium, Pseudomonas, and Pathogens e-coli.</td> </tr> <tr> <td>Post Filtration</td> <td>: Sand Filter, Activated Carbon Filter, Micron Filter-5 &10</td> </tr> <tr> <td>Design to Work</td> <td>: ULTRA VIOLET (UV) Optional</td> </tr> <tr> <td>Operating Mode</td> <td>: TDS up to 6000ppm, Hardness 3600mg/l</td> </tr> <tr> <td>Monitoring Accessories</td> <td>: Automatic + Manual</td> </tr> <tr> <td></td> <td>: Display/MMIC Panel, Pressure Gauges, Flow Meters etc.</td> </tr> </table>	<u>Description</u>	<u>Features</u>	Technology	: Membrane Based, (Size: 40x40)	Electricity	: 1680W/Ac-220v/440v, 50Hz	Pre Filtration	: Suspended Solids, Chemical Impurities, Bacteria like Cryptosporidium, Pseudomonas, and Pathogens e-coli.	Post Filtration	: Sand Filter, Activated Carbon Filter, Micron Filter-5 &10	Design to Work	: ULTRA VIOLET (UV) Optional	Operating Mode	: TDS up to 6000ppm, Hardness 3600mg/l	Monitoring Accessories	: Automatic + Manual		: Display/MMIC Panel, Pressure Gauges, Flow Meters etc.					
<u>Description</u>	<u>Features</u>																						
Technology	: Membrane Based, (Size: 40x40)																						
Electricity	: 1680W/Ac-220v/440v, 50Hz																						
Pre Filtration	: Suspended Solids, Chemical Impurities, Bacteria like Cryptosporidium, Pseudomonas, and Pathogens e-coli.																						
Post Filtration	: Sand Filter, Activated Carbon Filter, Micron Filter-5 &10																						
Design to Work	: ULTRA VIOLET (UV) Optional																						
Operating Mode	: TDS up to 6000ppm, Hardness 3600mg/l																						
Monitoring Accessories	: Automatic + Manual																						
	: Display/MMIC Panel, Pressure Gauges, Flow Meters etc.																						
<p><u>RO Plant 1000 LPH, Deluxe Model</u></p> <table border="0"> <tr> <td><u>Description</u></td> <td><u>Features</u></td> </tr> <tr> <td>Technology</td> <td>: Membrane Based, (Size: 40 x 40), Qty 4 Nos. (Dow, USA)</td> </tr> <tr> <td>Electricity</td> <td>: 3.5 KW/AC-220 - 440v, 50Hz</td> </tr> <tr> <td>Filtration</td> <td>: Suspended Solids, Chemical Impurities, Bacteria like Cryptosporidium, Pseudomonas, and Pathogens e-coli.</td> </tr> <tr> <td>Pre Filtration</td> <td>: Sand Filter, Activated Carbon Filter, Filters 5 & 10 Micron</td> </tr> <tr> <td>RO Piping</td> <td>: UPVC / SS 304 Optional</td> </tr> <tr> <td>Post Filtration</td> <td>: ULTRA VIOLET (UV) Optional</td> </tr> <tr> <td>Pumps, Skid</td> <td>: SS 304</td> </tr> <tr> <td>Design to Work</td> <td>: TDS up to 4000 ppm, Hardness 1000 ppm</td> </tr> <tr> <td>Operating Mode</td> <td>: Automatic + Manual</td> </tr> <tr> <td>Monitoring Accessories</td> <td>: Display/ DOL Panel, Pressure Gauges, Flow Meters etc.</td> </tr> </table>	<u>Description</u>	<u>Features</u>	Technology	: Membrane Based, (Size: 40 x 40), Qty 4 Nos. (Dow, USA)	Electricity	: 3.5 KW/AC-220 - 440v, 50Hz	Filtration	: Suspended Solids, Chemical Impurities, Bacteria like Cryptosporidium, Pseudomonas, and Pathogens e-coli.	Pre Filtration	: Sand Filter, Activated Carbon Filter, Filters 5 & 10 Micron	RO Piping	: UPVC / SS 304 Optional	Post Filtration	: ULTRA VIOLET (UV) Optional	Pumps, Skid	: SS 304	Design to Work	: TDS up to 4000 ppm, Hardness 1000 ppm	Operating Mode	: Automatic + Manual	Monitoring Accessories	: Display/ DOL Panel, Pressure Gauges, Flow Meters etc.	
<u>Description</u>	<u>Features</u>																						
Technology	: Membrane Based, (Size: 40 x 40), Qty 4 Nos. (Dow, USA)																						
Electricity	: 3.5 KW/AC-220 - 440v, 50Hz																						
Filtration	: Suspended Solids, Chemical Impurities, Bacteria like Cryptosporidium, Pseudomonas, and Pathogens e-coli.																						
Pre Filtration	: Sand Filter, Activated Carbon Filter, Filters 5 & 10 Micron																						
RO Piping	: UPVC / SS 304 Optional																						
Post Filtration	: ULTRA VIOLET (UV) Optional																						
Pumps, Skid	: SS 304																						
Design to Work	: TDS up to 4000 ppm, Hardness 1000 ppm																						
Operating Mode	: Automatic + Manual																						
Monitoring Accessories	: Display/ DOL Panel, Pressure Gauges, Flow Meters etc.																						

DATE:- _____

PLACE: _____

Signature of Tenderer _____

(NAME:- _____)

Address _____

